

FALL PROTECTION



SEALED BLOK™ SELF-RETRACTING LIFELINES - RETRIEVAL/BACKET

- 30' Sealed Blok™ self-retracting lifeline that features a retrieval bracket and swivelling snap hook with impact indicator
- 3-way emergency retrieval system
- New sealed design keeps the critical working components free of dirt, grease, water and chemicals
- Built-in carrying handle makes transport and anchoring safe and easy, and provides a secondary "dropped objects protection" attachment point
- Large pivoting anchorage handle stays in line with load for added security and allows use of a variety of connecting hardware
- Anti-ratcheting brake stops falls within inches and limits arresting forces to 900 lbs. for added safety
- Cast aluminum housing and heavy gauge steel end plates resist damage and provide corrosion resistance
- Self-locking swivel hook with impact indicator makes connections easy, and provides a visual means of inspection
- Certified to CSA standard Z259.2.2, Type 3 RSRL

Model No. SEB341
Mfg. No. 3400853C
Price/Each \$



MILLER® TRIPODS

The Miller® tripod is the anchorage connector for typical confined space and rescue systems.

- Lightweight, high-strength aluminum construction
- Adjustable legs with integral push pins, ideal for uneven surfaces
- Safety chain and tripod feet with rubber skid pads and serrated edge prevent slippage in icy conditions
- Independent leg locking feature holds legs securely in place
- Withstands up to 5000 lbs. (22 kN) of vertical pull
- Available with reflective tape
- Available in 7' (2 m)



Model No.	Mfg. No.	Description	Price /Each
SAK436	51/7FT	7' (2 m) High-Strength Aluminum Tripod	

Note: Available in 9' (2.7 m) upon request.

MANHANDLER® HOISTS/WINCHES

- Compact, durable steel construction
- Smooth, controlled winding action
- Effortless lifting and lowering with 5:1 gear ratio
- Anti-backlash crank handle braking system prevents free-wheeling
- Digital indicating system which counts drum turns in order to determine maintenance periodicity
- Built-in mounting bracket
- 3/16" galvanized steel cable
- 350 lbs. (1.6 kN) working capacity



Model No.	Mfg. No.	Description	Price /Each
SAR489	8442-27/65FT	ManHandler® Hoist w/ 65 ft. 3/16" Galvanized Steel Cable	
SAR490	8442-27/100FT	ManHandler® Hoist w/ 100 ft. 3/16" Galvanized Steel Cable	

SEALED SELF-RETRACTING LIFELINE W/RETRIEVAL WINCH

- This sealed SRL incorporate a revolutionary patented concept that separates all dynamic components from foreign elements such as grease, moisture and dirt, ensuring your SRL is always operating at peak efficiency, no matter how dirty or damp your environment
- Incorporates a self contained bi-directional retrieval winch suitable for raising and lowering personnel in emergency rescue/retrieval situations
- Winch drive incorporates and overload device thus reducing the possibility of injury should the worker become entangled during retrieval
- Input crank handle brake will prevent movement of the load if the operator accidentally released the handle during raising/lowering
- In the event of a fall, the self adjusting disk brake will stop the fall and limit the arresting forces imposed on the worker to 900 lbs. or less
- Incorporates a quick-mount bracket that enables the user to attach it to a DBI/SALA support structure (tripod, davit arm, etc.) with ease
- Swivelling anchorage loop to prevent twisting of lifeline
- Self-locking swivel snap hook with impact indicator
- Reserve lifeline retention system for added safety
- 50 ft. 3/16" galvanized steel wire rope for durability
- Stainless steel and cast aluminum housing for corrosion resistance
- Certified to CSA standard Z259.2.2, Type 3 RSRL



Model No.	Mfg. No.	Description	Price /Each
SEN426	3400923C	15 m (50') Sealed SRL	
SEH133	8301050	15 m (50') Sealed SRL w/7' Aluminum Tripod	

ADVANCED DIGITAL SERIES WINCHES

- Performs both descent and retrieval functions
- Removable aluminum crank handle
- Utilizes both 9:1 and 4:1 drives
- Capable of average speeds from 4 m/min (13 ft/min) up to 9 m/min (30 ft/min)
- Manually operated by simply rotating the handle to raise or lower personnel or materials
- Features a self-locking swivel snap hook
- Built-in mounting bracket
- 60' x 1/4" galvanized cable

Model No. SEJ417
Mfg. No. 8518560
Price/Each \$



CONFINED SPACE RESCUE KITS

- Ready-to-use combination of North equipment for rescue, entry/egress
- 7' portable tripod with safety chain around legs
- 3-way self-retracting lifeline with cast aluminum housing – 50' stainless steel cable 3/16"
- Capacity: 310 lbs. (140 kg)
- Kit includes: Tripod, 3-Way SRL, Mounting Bracket, and Carrying Bag
- Workload winch and winch mounting bracket sold separately



Model No.	Mfg. No.	Description	Price /Each
SN130	FP664155R	Confined Space Kit	
SA0558	FP2/7155R	Retrieval Winch	
SAH548	FP6610/15	Winch Mounting Bracket	